

Pressure Switch 312200



Recycling Equipment Corporation

BARKSDALE_PRESSU_49f07d494c59c.jpg



Single Pressure Switch Adustable 250-3000 PSI

Rating: Not Rated Yet

Price

Sales price \$441.00

Sales price without tax \$441.00

Tax amount

[Ask a question about this product](#)

Description

270000 Hydraulic Pressure Switch. Commonly used on many balers and compactors from 1980-2010. Adjustable from 250-3000psi, proof rated 7000psi, N.O.-N.C. contacts rated at 10amp@125v, 1/4" NPT female fluid connection. With mounting bracket and 18" molded leads. Very commonly used on many different hydraulic power units. C9612-3



General Specifications

Electrical Characteristics:	All models incorporate Underwriters Laboratories, Inc. and CSA Listed single pole double throw snap-action switching elements
Accuracy:	±2% of the adjustable range
Switch:	10 amps @ 125, 250, or 480 VAC; 0.03 amps @ 250 VDC, Class B limit switch
Type:	
Rating:	
Wetted Parts:	Nickel plated aluminum
Process Fitting:	Buna-N (standard)
O-ring:	416 stainless steel
Piston:	Anodized aluminum

270000 Baler Pressure Switch

Enclosure:

Electrical Connection: 18" free leads (terminal block on "T" model)

Enclosure Ratings: NEMA 3

Pressure Connection: 1/4" - 18 NPT female

Approvals: UL File E42816

UL/CSA (optional): Class 3231 02, File No. 022355-0-000

Temperature Range: -20° to +165°F (-29° to +74°C)

Operating: -40° to +200°F (-40° to +93°C)

Storage:

Adjustment Instructions: With screwdriver, turn adjustment screw counterclockwise to increase and clockwise to decrease the actuation point.
Barksdale

//