Signal Horn for Balers



SIGNAL_HORN___FE_4c8f8d36b4003.jpg



Commonly Used on Balers

Rating: Not Rated Yet

Price

Sales price \$142.00

Sales price without tax \$142.00

Tax amount

Ask a question about this product

Description

VIBRATONE HORN, 120VAC 50/60HZ 0.18a, 200' RANGE CODED OR SUSTAINED TONES

Information

- 12~240 VAC
- 94~100 dB at 10 Ft
- Up to 200-ft. Range
- UL; cUL; CSA; FM Approvals
- Coded or Sustained Tones

Vibratone horns produce a very loud horn tone by the electro?mechanical vibration of a diaphragm. Capable of reproducing coded blasts or sustained tones, Federal Signal Model 350 Vibratone horns are excellent for general alarm, start and dismissal, coded paging, and process control signaling in area of high ambient noise levels.

Vibratone mounting options provide for surface, flush or semi?flush mounting on walls, panels, in cabinets, on 4?inch square outlet boxes, or in concrete and deep wall constructions.

Each Vibratone horn is enclosed in a zinc die?cast housing and sealed with gray powder?coat paint. The Model features a stainless steel diaphragm. The rugged construction resists vandalism and the effects of harsh industrial environments.

Compact size, loud output and heavy?duty construction make the Model 350 Vibratone horns ideal for industrial and institutional signaling applications.

//